

1	Unique identification code: IKO MONO STICK SARKING 4000		
2	Intended use : Underlays for discontinuous roofing		
3	Manufacturer : IKO S.A.S - Z.I du Moulin, B.P. 162 - 76410 TOURVILLE LA RIVIERE-FRANCE – www.iko.fr/dop.		
4	Authorised representative : Not applicable.		
5	Systems of assessment and verification of constancy of performance of the product : System 3.		
6	a) Harmonised standard : EN 13859-1 June 2010 Notified body : N°0071, Laboratoire National de métrologie et d'Essais (LNE) b) European Assessment Documentation : Not applicable		
7	Declared performance :		
	Essential characteristics	Performance	Harmonised technical specification
	Reaction to fire	NPD	EN 13859-1:2010
	Water tightness	W1	
	Tensile properties : Maximum tensile force	L = 760 N/50mm ± 200 N/50mm T = 730 N/50mm ± 200 N/50mm	
	Tensile properties : Elongation at maximum tensile force	L = 45 % ± 20 % T = 50 % ± 20 %	
	Resistance to tearing	L = 250 N/50mm ± 100 N/50mm T = 300 N/50mm ± 150 N/50mm	
	Low temperature flexibility	≤ -15°C	
	Durability: Artificial ageing behavior, concerning : - Water tightness - Tensile properties : Maximum tensile force	W1 L = 760 N/50mm ± 200 N/50mm T = 730 N/50mm ± 200 N/50mm	
	- Tensile properties : Elongation at maximum tensile force	L = 45 % ± 20 % T = 50 % ± 20 %	
	Dangerous substances	Conform ⁽¹⁾ ⁽²⁾	
	NPD = No performance determined ⁽¹⁾ This product does not contain asbestos or tar constituents. ⁽²⁾ In the absence of European harmonized test methods, verification and declaration on release / content has to be done taking into account national provisions in the place of use.		
8	Appropriate technical documentation and / or specific technical documentation: not applicable		

The performance of the product identified above are consistent with the declared performance. In accordance with Regulation (EU) No 305/2011, this declaration of performance is issued under the sole responsibility of the manufacturer mentioned above.

Signed for and on behalf of the manufacturer by:
M. Benoit STEINER, Chief Executive.
Tourville-La-Rivière, 14/02/20

