

|   |                                                                                                                                                                                                                                                                                                                   |                                                                     |                                           |
|---|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------|-------------------------------------------|
| 1 | <b>Unique identification code:</b><br>IKO MONO STICK SARKING 2500                                                                                                                                                                                                                                                 |                                                                     |                                           |
| 2 | <b>Intended use :</b><br>Underlays for discontinuous roofing                                                                                                                                                                                                                                                      |                                                                     |                                           |
| 3 | <b>Manufacturer :</b><br>IKO S.A.S - Z.I du Moulin, B.P. 162 - 76410 TOURVILLE LA RIVIERE-FRANCE – www.iko.fr/dop.                                                                                                                                                                                                |                                                                     |                                           |
| 4 | <b>Authorised representative :</b><br>Not applicable.                                                                                                                                                                                                                                                             |                                                                     |                                           |
| 5 | <b>Systems of assessment and verification of constancy of performance of the product :</b><br>System 3.                                                                                                                                                                                                           |                                                                     |                                           |
| 6 | <b>a) Harmonised standard :</b><br>EN 13859-1 June 2010<br><b>Notified body :</b><br>N°0071, Laboratoire National de métrologie et d'Essais (LNE)<br><b>b) European Assessment Documentation :</b><br>Not applicable                                                                                              |                                                                     |                                           |
| 7 | <b>Declared performance :</b>                                                                                                                                                                                                                                                                                     |                                                                     |                                           |
|   | <b>Essential characteristics</b>                                                                                                                                                                                                                                                                                  | <b>Performance</b>                                                  | <b>Harmonised technical specification</b> |
|   | Reaction to fire                                                                                                                                                                                                                                                                                                  | NPD                                                                 | EN 13859-1:2010                           |
|   | Water tightness                                                                                                                                                                                                                                                                                                   | W1                                                                  |                                           |
|   | Tensile properties : Maximum tensile force                                                                                                                                                                                                                                                                        | L = 580 N/50mm ± 160 N/50mm<br>T = 430 N/50mm ± 70 N/50mm           |                                           |
|   | Tensile properties : Elongation at maximum tensile force                                                                                                                                                                                                                                                          | L = 35 % ± 15 %<br>T = 30 % ± 15 %                                  |                                           |
|   | Resistance to tearing                                                                                                                                                                                                                                                                                             | L = 200 N/50mm ± 50 N/50mm<br>T = 250 N/50mm ± 100 N/50mm           |                                           |
|   | Low temperature flexibility                                                                                                                                                                                                                                                                                       | ≤ -15°C                                                             |                                           |
|   | Durability:<br>Artificial ageing behavior, concerning :<br>- Water tightness<br><br>- Tensile properties : Maximum tensile force                                                                                                                                                                                  | W1<br><br>L = 580 N/50mm ± 160 N/50mm<br>T = 430 N/50mm ± 70 N/50mm |                                           |
|   | - Tensile properties : Elongation at maximum tensile force                                                                                                                                                                                                                                                        | L = 8 % ± 4 %<br>T = 30 % ± 10 %                                    |                                           |
|   | Dangerous substances                                                                                                                                                                                                                                                                                              | Conform <sup>(1)</sup> <sup>(2)</sup>                               |                                           |
|   | NPD = No performance determined<br><sup>(1)</sup> This product does not contain asbestos or tar constituents.<br><sup>(2)</sup> In the absence of European harmonized test methods, verification and declaration on release / content has to be done taking into account national provisions in the place of use. |                                                                     |                                           |
| 8 | <b>Appropriate technical documentation and / or specific technical documentation:</b><br>not applicable                                                                                                                                                                                                           |                                                                     |                                           |

The performance of the product identified above are consistent with the declared performance. In accordance with Regulation (EU) No 305/2011, this declaration of performance is issued under the sole responsibility of the manufacturer mentioned above.

Signed for and on behalf of the manufacturer by:  
M. Benoit STEINER, Chief Executive.  
Tourville-La-Rivière, 14/02/20

