

Declaration of Performance

N°ELAS021-13707 (version 7)

ı	Unique identification code: MEPALU 4000 EQUATORIAL		
	Intended use :		
2	Reinforced bitumen sheets for roof waterproofing	1	
	Manufacturer:		
3 IKO S.A.S - Z.I du Moulin, B.P. 162 - 76410 TOURVILLE LA RIVIERE - FRANCE			ko.fr/dop.
	Authorised representative :		
	Not applicable. System of assessment and verification of constancy of performance of the product :		
	System 2+.		
	a) Harmonised standard: EN 13707:2004+A2 July 2009. Notified body: N°0958, SGS INTRON Certificate B.V. b) European Assessment Documentation:		
	Not applicable		
	Declared performance :	<u></u>	
	Essential characteristics	Performance	Harmonised technical specification
	External fire performance	F _{ROOF} (t1,t2,t3,t4) ⁽¹⁾	
	Reaction to fire	NPD	
	Neaction to life	INI D	
	Watertightness	Pass	
	Tensile properties : Maximum tensile force	L = 900 N/50mm ± 200 N/50mm	
	rensile properties : Maximum tensile force	L = 900 N/50mm + 200 N/50mm T = 710 N/50mm + 100 N/50mm	
	Tensile properties : Elongation at maximum	L & T = 37 % ± 10 %	
	tensile force		
•	Root resistance	NPD	
	Resistance to static loading method A	≥ 25 kg	EN 13707:2004+A2:2009
	Resistance to impact method B	≥ 2000 mm	
		_	
	Resistance to tearing	L & T= 400 N/50mm <u>+</u> 100 N/50mm	
	Peel resistance of joints	L = 225 N/50mm <u>+</u> 35 N/50mm	
	<u>-</u>	T = 160 N/50 mm + 35 N/50 mm	
	Shear resistance of joints	L = 900 N/50mm <u>+</u> 200 N/50mm	
		T = 710 N/50mm <u>+</u> 100 N/50mm	
	Durability		
	- Pliability after heat oven exposure	0°C <u>+</u> 5°C	
	- Heat flow after heat oven exposure	95°C <u>+</u> 5°C	
	Pliability	≤ -5 °C	
ŀ	Dangerous substances	Conform (2) (3)	
	NPD = No performance determined		
	(1) As the resistance to external fire exposure of roof depends on the complete system, no performance can be declared		
	for the product alone.		
	(2) This product does not contain asbestos or tar constituents.		
	(3) In the absence of European harmonized test methods, verification and declaration on release / content has to be done		
	taking into account national provisions in the place of use.		

The performance of the product identified above are consistent with the declared performance. In accordance with Regulation (EU) No 305/2011, this declaration of performance is issued under the sole responsibility of the manufacturer mentioned above.

Signed for and on behalf of the manufacturer by: M. Benoit STEINER, Chief Executive. Tourville-La-Rivière, 24/02/20



not applicable