

1	Unique identification code: IKO EQUERRE 100		
2	Intended use : Bitumen damp proof sheets type A		
3	Manufacturer : IKO S.A.S - Z.I du Moulin, B.P. 162 - 76410 TOURVILLE LA RIVIERE-FRANCE – www.iko.fr/dop.		
4	Authorised representative : Not applicable.		
5	Systems of assessment and verification of constancy of performance of the product : System 2+		
6	a) Harmonised standard : EN 13969 december 2004 + Amendement A1 november 2006 Notified body : N°0958, SGS INTRON Certificate B.V. N°0679, CSTB b) European Assessment Documentation : Not applicable		
7	Declared performance :		
	Essential characteristics	Performance	Harmonised technical specification
	Reaction to fire	NPD	EN 13969:2004/A1:2006
	Watertightness	Pass	
	Tensile properties : Maximum tensile force	L = 750 N/50mm ± 200 N/50mm T = 550 N/50mm ± 150 N/50mm	
	Tensile properties : Elongation at maximum tensile force	L = 40 % ± 15 % T = 45 % ± 10 %	
	Resistance to static loading method A	≥ 20 kg	
	Resistance to impact method B	≥ 1250 mm	
	Resistance to tearing	L & T = 300 N/50mm ± 150 N/50mm	
	Shear resistance of joints	NPD	
	Durability (watertightness) - against artificial ageing/degradation - against chemical	Pass NPD	
	Pliability	≤ -15°C	
	Dangerous substances	Conform ⁽²⁾ ⁽³⁾	
	NPD = No performance determined ⁽¹⁾ As the resistance to external fire exposure of roof depends on the complete system, no performance can be declared for the product alone. ⁽²⁾ This product does not contain asbestos or tar constituents. ⁽³⁾ In the absence of European harmonized test methods, verification and declaration on release / content has to be done taking into account national provisions in the place of use.		
8	Appropriate technical documentation and / or specific technical documentation: not applicable		

The performance of the product identified above are consistent with the declared performance. In accordance with Regulation (EU) No 305/2011, this declaration of performance is issued under the sole responsibility of the manufacturer mentioned above.

Signed for and on behalf of the manufacturer by:
M. Benoit STEINER, Chief Executive.
Tourville-La-Rivière, 21/02/23

