

DECLARATION OF PERFORMANCE



N°: IKO VAP ALPA ALU 3 en 1 NH 001 EN

1. Identification code IKO VAP ALPA ALU 3 en 1
2. Intended use Bitumen water vapour control layers
3. Manufacturer IKO-AXTER
6, rue Laferrière
75009 Paris
France
www.iko.fr/dop
4. Authorised representative NA
5. System of assessment and verification of constancy of performance of the product Système 3
- 6a. Product covered by the harmonised standard: EN 13970
Declaration of the performance of the essential characteristics by the manufacturer
- 6b. European Technical Assessment : NA
7. Declared performance

Essential characteristics		Performance			Units	Harmonised technical specification
		Value	Tolerance			
			Min	Max		
Resistance to tearing (nail shank)	Longitudinal direction	150	50	-	N	EN 13970:2005/A1:2007
	Cross direction	150	50	-		
Tensile properties : maximum tensile force	Longitudinal direction	550	300	-	N/50mm	
	Cross direction	350	250	-		
Tensile properties : maximum elongation	Longitudinal direction	15	5	-	%	
	Cross direction	40	15	-		
Watertightness under 2 kPa		Conform			-	
Water vapour transmission properties		≥ 1000			m	
Durability EN 1296	Water vapour transmission	≥ 1000			m	
Durability EN 1847	Water vapour transmission	NPD			m	
Reaction to fire		NPD			-	
Dangerous substances		Note 1 and 2			-	

NA: not applicable due to use of product.

Note 1 : This product does not contain asbestos or tar constituents

Note 2 : In the absence of European harmonized test methods, verification and declaration on release/content has to be done taking into account national provisions in the place of use.

The performances of the product identified above are in conformity with the declared performances.

In accordance with Regulation (UE)n°305/2011 , this declaration of performance is issued under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:
Peter Fleischmann (Managing Director)

Paris
29/09/2023