

N°: IKO EQUERRE 100 NH 001 EN

1. Identification code: IKO EQUERRE 100
2. Intended use: Reinforced bitumen sheets for roof waterproofing
Bitumen damp proof sheets including bitumen basement tanking sheets
3. Manufacturer: IKO-AXTER
6, rue Laferrière
75009 Paris
France
www.iko.com/dop
4. Authorised representative: NA
5. System of assessment and verification of constancy of performance of the product: System 2+
- 6a. Product covered by the harmonised standard: EN 13707
The CSTB, notify body n° 0679 has performed under system 2+ the initial inspection of factory production control the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control n° 0679 - CPR - 0128.
The SGS INTRON Certificatie B.V, notify body n° 0958 has performed under system 2+ the initial inspection of factory production control the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control n° 0958-CPR-2016/3.
EN 13969
The CSTB, notify body n° 0679 has performed under system 2+ the initial inspection of factory production control the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control n° 0679 - CPR - 0129.
The SGS INTRON Certificatie B.V, notify body n° 0958 has performed under system 2+ the initial inspection of factory production control the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control n° 0958-CPR-2016/3.
- 6b. European Technical Assessment : NA
7. Declared performance

Essential characteristics			Performance			Harmonised technical specification
			Value	Tolerance		
				Min	Max	
Resistance to tearing (nail shank)	Longitudinal direction		300	150	-	N
	Cross direction		300	150	-	
Tensile properties : maximum tensile force	Longitudinal direction		500	350	-	N/50mm
	Cross direction		400	250	-	
Tensile properties : maximum elongation	Longitudinal direction		40	30	-	%
	Cross direction		50	40	-	
Shear resistance of joint	Maximum force	Selvedge	NA	-	-	N/50mm
		End joint	NA	-	-	
Flexibility at low temperature			≤ -15			°C
Resistance to impact (method A)			≥ 500			mm
Reaction to fire			NPD			-
Dangerous substances			Note 2 and 3			-
Peel resistance of joint	Maximum force	Selvedge	NA	-	-	N/50mm
		End joint	NA	-	-	
Resistance to static loading (method A)			≥ 15			kg
Durability EN 1296	Flow resistance at elevated temperature		NA	-	-	°C
Durability EN 1297	Visible defects		NA			
Watertightness under 10 kPa			Conform			-
Resistance to root penetration			NA			-
Resistance to external fire exposure			FRoof (Note 1)			-
Resistance to static loading (method B)			≥ 5			kg
Watertightness under 60 kPa			Conform			-
Durability EN 1296	Watertightness		Conform			-
Durability EN 1847	Watertightness		NPD			-

NA: not applicable due to use of product.

Note 1 : As the resistance to external fire exposure of roof depends on the complete system, no performance can be declared for the product alone.

Note 2 : This product does not contain asbestos or tar constituents

Note 3 : In the absence of European harmonized test methods, verification and declaration on release/content has to be done taking into account national provisions in the place of use.

The performances of the product identified above are in conformity with the declared performances.

In accordance with Regulation (UE)n°305/2011 , this declaration of performance is issued under the sole responsibility of the manufacturer identified above

Signed for and on behalf of the manufacturer by:
Peter Fleischmann (Managing Director)

Paris
23/10/2023

