

**N°: IKO MONO GREEN ALPA 3000 AR/F NH 001 EN**

- 1. Identification code** IKO MONO GREEN ALPA 3000 AR/F
- 2. Intended use** Reinforced bitumen sheets for roof waterproofing  
Bitumen damp proof sheets including bitumen basement tanking sheets
- 3. Manufacturer** IKO-AXTER  
6, rue Laferrière  
75009 Paris  
France  
www.iko.com/dop
- 4. Authorised representative** NA
- 5. System of assessment and verification of constancy of performance of the product** System 2+
- 6a. Product covered by the harmonised standard:** EN 13707  
The CSTB, notify body n° 0679 has performed under system 2+ the initial inspection of factory production control the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control n° 0679 - CPR - 0128.  
EN 13969  
The CSTB, notify body n° 0679 has performed under system 2+ the initial inspection of factory production control the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control n° 0679 - CPR - 0129.
- 6b. European Technical Assessment :** NA

**7. Declared performance**

Essential characteristics			Performance				Harmonised technical specification
			Value	Tolerance		Units	
				Min	Max		
Resistance to tearing (nail shank)	Longitudinal direction		200	180	-	N	EN 13707+A2:2009 EN 13969:2005/A1:2007
	Cross direction		250	230	-		
Tensile properties : maximum tensile force	Longitudinal direction		600	500	-	N/50mm	
	Cross direction		600	500	-		
Tensile properties : maximum elongation	Longitudinal direction		35	25	-	%	
	Cross direction		35	25	-		
Shear resistance of joint	Maximum force	Selvedge	600	500	-	N/50mm	
		End joint	600	500	-		
Flexibility at low temperature			≤ -14			°C	
Resistance to impact (method A)			≥ 600			mm	
Reaction to fire			NPD			-	
Dangerous substances			Note 2 and 3			-	
Peel resistance of joint	Maximum force	Selvedge	NA	-	-	N/50mm	EN 13707+A2:2009
		End joint	NA	-	-		
Resistance to static loading (method A)			≥ 20			kg	
Durability EN 1296	Flow resistance at elevated temperature		120	110	-	°C	
Durability EN 1297	Visible defects		NA				
Watertightness under 10 kPa			Conform			-	
Resistance to root penetration			Conform			-	
Resistance to external fire exposure			FRoof (Note 1)			-	
Resistance to static loading (method B)			≥ 5			kg	
Watertightness under 60 kPa			Conform			-	
Durability EN 1296	Watertightness		Conform			-	EN 13969:2005/A1:2007
Durability EN 1847	Watertightness		NPD			-	

NA: not applicable due to use of product.

Note 1 : As the resistance to external fire exposure of roof depends on the complete system, no performance can be declared for the product alone.

Note 2 : This product does not contain asbestos or tar constituents

Note 3 : In the absence of European harmonized test methods, verification and declaration on release/content has to be done taking into account national provisions in the place of use.

The performances of the product identified above are in conformity with the declared performances.

In accordance with Regulation (UE)n°305/2011 , this declaration of performance is issued under the sole responsibility of the manufacturer identified above

Signed for and on behalf of the manufacturer by:  
Peter Fleischmann (Managing Director)

Paris  
23/10/2023

